

PRODUCT DATASHEET

DL IP44 FRAME DN 190 WT

DOWNLIGHT IP44 | Downlights with IP44 grade



Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Shops
- Bathrooms

Product benefits

- Easily installed

Product features

- Robust polycarbonate casing
- Mounting accessories included



TECHNICAL DATA

Dimensions & Weight

Diameter	190 mm
Height	47 mm
Product weight	165.00 g





Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Mounting type	Surface
Mounting location	Ceiling

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Tender documents

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075709942	Folding box 1	195 mm x 53 mm x 199 mm	226.00 g	2.06 dm ³
4058075709959	Shipping box 10	400 mm x 279 mm x 215 mm	2676.00 g	23.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



Model	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	g [mm]	h [mm]	n [mm]
DL IP44 DN190	195	142	200	147	3-25	68	42	152	170
DL IP44 DN116	100	53	116	53	3-25	68	42	152	170
DL IP44 DN166	180	143	181	143	3-25	68	42	152	170
DL IP44 DN190	116	108	190	108	3-25	68	42	152	170
DL IP44 DN216	200	154	216	154	3-25	68	42	152	170

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.