



HB 601

312181.002 | Recessed modular luminaires



4051859221562
LED
L 595, B 595,



Frame: white powder-coated aluminium. Diffuser: plastic (PMMA), microprismatic/opal. Lateral LED light injection. LED included. External control gear (32mm high). Accessories for surface or pendant mount must be ordered separately.

Colour

Colour white

Dimensions

Length L 595 mm
Width B 595 mm
Recess height HE 42 mm
Weight 3,75 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Lifetime 50000 h

Lighting technology

Beam Angle 87°/84°
Photobiological safety according to EN 62471 Risk group 0

Electrical

Control gear Converter
Voltage 200 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 20
Luminaires on B16A fuse 32
Inrush current / inrush current duration 10.5 A / 89 µs
System power 1 35 W
Rated luminous flux 1 3.350 lm
Glare evaluation UGR (4H 8H) 1 17,9
Luminaire efficacy 1 96 lm/W

Approbations

Type of Protection	IP 40
Protection Class	II
Safety marks	F-mark
Other Marks	WEEE mark
country of origin	CE
Energy efficiency class LED	A+
Energy class of included lamp	A+

Accessories

981978.000	Pendant kit , LP 1500 consisting of 4 steel ropes (L 1500) and ceiling mounting sets for quick adjustment of the ropes
981980.012	Ceiling surface mounting kit consisting of 4 cylindrical spacers (Ø 30, H 38) for module 600 / 1200
981941.002	Mounting frame for installation in suspended ceilings L 624, B 624, H 2, HE 94 for module 600
982187.022	Surface mounting frame L 602, B 602, H 47 for module 600