

Product datasheet

Specifications



Front Plate, PrismaSeT P & G, 8M, for Transfer Pact, 160A, 3P/4P, vertical fixed, W650mm

LVS03207

Main

Range	TransferPacT
Range of product	PrismaSeT G Active PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory Spare part
Range compatibility	PrismaSeT PrismaSeT G Active TP automatic transfer switch PrismaSeT PrismaSeT P Active PrismaSeT PrismaSeT G PrismaSeT PrismaSeT P
Type of front plate	Cut-out plate
type of front plate	Cut-out
Installed device	PrismaSeT Active: panel mounting terminal blocks integrated earth leakage protection - control: 1 key switch - vertical installation
Poles description	1 x 3P or 4P: mounting plate support vertical installation
Operating position	Vertical

Complementary

Enclosure/cubicle description	2 floor-standing enclosure - width 650 + 150 mm depth 400 mm 2 floor-standing enclosure + duct - width 650 mm depth 400 mm 2 floor-standing enclosure - width 600 mm depth 200 mm
Connection position	Direct connection
Number of horizontal rows	1
Number of vertical modules [50 mm]	8
Standards	IEC 60947
Material	Carbon steel
Protective treatment	Epoxy powder coat
Surface finish	Matt
Width	499 mm
Height	399 mm
Depth	14 mm
Product weight	1.2 kg
Quantity per set	1 kit

functional unit	650 + 150 mm 400 mm PrismaSeT G Active 2 floor-standing enclosure terminal blocks integrated vertical 1 key switch horizontal 3P or 4P 1 direct 650 + 150 mm 400 mm PrismaSeT G Active 2 floor-standing enclosure terminal blocks integrated vertical 1 key switch horizontal 3P or 4P 1 direct 8 650 mm 400 mm PrismaSeT P Active 2 floor-standing enclosure + duct 600 mm 200 mm PrismaSeT G
------------------------	---

Environment

IP degree of protection	IP31
IK degree of protection	IK10
Ambient air temperature for storage	0...28 °C
Ambient air temperature for operation	25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	40.500 cm
Package 1 Length	50.000 cm
Package 1 Weight	1.538 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	10.500 cm
Package 2 Width	43.000 cm
Package 2 Length	53.000 cm
Package 2 Weight	9.700 kg
Unit Type of Package 3	P12
Number of Units in Package 3	12
Package 3 Height	23.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	31.000 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No