

Product datasheet

Specifications



Mounting Plate, PrismaSeT G, for Transfer Pact, 160A, 3P/4P, vertical fixed, W600

LVS03427

Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT G Active
Device short name	TP
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT G TP mounting plate
installation description	Cubicle - width 600 mm Cubicle - width 600 mm depth 200 mm Cubicle - width 850 mm depth 200 mm
Enclosure mounting	Surface
Mounting location	Top and bottom front of enclosure
Mounting plate description	Dedicated
Type of rail	Modular Adjustable symmetrical DIN rail
Installed device	Fixed with earth leakage protection - vertical installation
Poles description	1 x 3P or 4P: panel mounting terminal blocks vertical installation
Condition of using cable tie	-20-70 °C (8M high) when installation of device is in vertical
Number of vertical modules [50 mm]	8 module(s): terminal blocks integrated earth leakage protection , comb busbar in 600 mm Wide2 floor-standing enclosure (cable coming from top and bottom of enclosure) 8 module(s): terminal blocks integrated earth leakage protection , comb busbar in 850 mm Wide2 floor-standing enclosure + duct (cable coming from top and bottom of enclosure)
Standards	IEC 61439-2
Product certifications	IEC

Complementary

Connections - terminals	4 screw terminals terminal blocks switch
Cable entry	Top and bottom 0...70 mm in front of support frame
Material	On mounting holes: stainless steel
Protective treatment	None
Width	470 mm
Height	224 mm
Depth	61 mm
Product weight	2 kg

Quantity per set	1 kit
------------------	-------

Environment

IP degree of protection	IP31 0...50 °C conforming to IEC 61439-2
-------------------------	--

IK degree of protection	IK10 conforming to IEC 60947
-------------------------	------------------------------

Mechanical robustness	IK protection 25...55 °C, RH 95 % - - 20...55 °C conforming to IEC 61439-2
-----------------------	--

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	6.000 cm
------------------	----------

Package 1 Width	23.000 cm
-----------------	-----------

Package 1 Length	47.000 cm
------------------	-----------

Package 1 Weight	1.746 kg
------------------	----------

Unit Type of Package 2	P12
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	32.500 cm
------------------	-----------

Package 2 Width	80.000 cm
-----------------	-----------

Package 2 Length	120.000 cm
------------------	------------

Package 2 Weight	37.820 kg
------------------	-----------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No