



Principal

Gama	ClimaSys
Nume produs	ClimaSys CV
Tip produs sau componenta	Ventilator
Type of filter	Standard
Flow rate	Free flow rate with standard filter 38 m ³ /h la 50 Hz Free flow rate with standard filter 39 m ³ /h la 60 Hz
[Us] tensiune de alimentare nominala	150...250 V
Tensiune de intrare	230 V 50/60 Hz

Suplimentar

Absorbed power	4.5 W 50 Hz 4.8 W 60 Hz
[In] curent nominal	0,16 A 50 Hz 0,17 A 60 Hz
Noise level < at	40...41 dB
Tip rulment	Minge
Inaltime	External 137 mm
Adancime	External 117 mm
Adancime	External 49 mm
Dimensiuni decupaj	92 x 92 mm
Greutate produs	0,22 kg
Material	Outlet grille injected thermoplastic (ASA PC)
Culoare	Outlet grille gri (RAL 7035)
Temperatura ambientala de functionare	-10...70 °C
Temperatura de depozitare	-40...70 °C
Presiune maxima	29 Pa flow rate 0 m ³ /h
Conexiuni - borne	Cablu
Grad de protectie IP	IP54
Compozitie dispozitiv	1 axial motor 2 protective grille on the front and rear surfaces 1 filtru front of axial motor

	1 outlet grille frontal 1 cut-out template
Conditii de utilizare	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided

Packing Units

Tip unitate a formei de impachetare 1	PCE
Număr de produse în pachet	1
Greutate colet(Lbs)	291,75 g
Înălțimea formei de impachetare 1	7 cm
Latimea formei de impachetare 1	12,5 cm
Lungimea formei de impachetare 1	14,5 cm

Offer Sustainability

Stare ofertă sustenabilă	Produs Green Premium
Regulamentul REACH	Declaratia REACH
Conform REACH fara SVHC	Da
Directiva RoHS UE	Conform Declaratia RoHS UE
Fara mercur	Da
Informatii privind scutirea de la RoHS	Da
Regulamentul RoHS China	Declaratia RoHS China Produs in afara domeniului de aplicare a RoHS China. Declaratia privind substantele in scop informativ.

Contractual warranty

Garantie	18 months
----------	-----------