

XTINY RECESSED|SURFACE

ARELUX S.R.L.
Alexei Tolstoi street, nr. 12, Bacău - 600093, ROMÂNIA.
Tel: +40 0234 514 492 / 546 620. Fax: +40 0234 546 677.

XT01SLC SBK

www.arelux.ro

10/2023

GENERAL INFORMATION / INFORMAȚII GENERALE / INFORMAZIONI GENERALI

Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Operating temp.	Weight
XT01SLC SBK	Sand black	-	-	48V DC	-	-	-	-	-	-	-	-30 ÷ +45 °C	0,02 kg

Description / Descriere / Descrizione

EN - Linear connector, mechanical and electrical, for two surface XTINY profiles.

RO - Conector liniar, mecanic și electric, pentru două profile aparente XTINY.

IT - Connettore lineare, meccanico ed elettrico, per due profili XTINY da superficie.

Housing / Corp / Corpo

EN - Housing of Sand black polycarbonate.

RO - Carcasa din policarbonat de culoare neagră, finisaj sablat.

IT - Carcassa in policarbonato nero sabbiato.

Electric gear / Aparataj de alimentare / Alimentazione

EN - Electrical circuit for 48V DC with two electrical contacts at each end.

RO - Circuit electric de 48V DC cu cate două contacte electrice la fiecare capăt.

IT - Circuito elettrico per 48V DC con due contatti elettrici a ciascuna estremità.

