


## MÉDARD RECESSED 42 LED GE

Médard recessed broadens the variety of applications. In contrast to the rest of the family, Médard recessed's light source is fixed, emanating a medium or flood beam angle. Hospitality environments including wellness centers, and high-end residential spaces, including bathrooms, will be spot-on locations for this IP55-rated new family member.

Art. Nr. 11550009

### SPECIFICATIONS

Lamp	1x LED Module	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 40 h 65	
Weight	0.11kg	
Min. distance	0.1 m	
IP	IP55	
Glow wire test	960°	
Lifetime	50000 hrs	
CRI	90	
webterm_cie	100/100/100/100/76	
Power supply	350mA	500mA
	8.5Vf	8.8Vf
Connected load	3W	4.3W
Lumen	259lm	349lm
Efficacy	86lm/W	81lm/W
UGR	11	12
	Adjustability Not Applicable	



Available label  
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11550032	11550132	11550232	11550332
white struc	11550009	11550109	11550209	11550309

