



<b>SKU</b>	: 2.011E0A930003000000
<b>Installation Method</b>	: Track Mounted
<b>Housing Material</b>	: Die Cast Aluminum
<b>Housing Colour</b>	: White (RAL 9003)
<b>Adjustability</b>	: 350° rotational and 90° tiltable
<b>Optic</b>	: Facet Anodized Aluminum Reflector
<b>Beam Angle [deg]</b>	: 30°
<b>System Power [W]</b>	: 30W
<b>Luminous Flux [lm]</b>	: 3000lm
<b>System Efficiency [lm/W]</b>	: 100lm/W
<b>CCT [K]</b>	: 3000K
<b>CRI [Ra]</b>	: (Ra) >90
<b>Chromaticity Tolerance</b>	: 3
<b>Mains Voltage [VAc]</b>	: 220-240V / 50-60Hz
<b>Ambient Temperature [degC]</b>	: 35°C
<b>Ingress Protection</b>	: IP20
<b>Light Source Energy Class</b>	: E
<b>Light Source Identifier</b>	: 929001590506
<b>Lifetime/Failure Rate [h]</b>	: >100000h/L80B20 / >50000h/L90B50
<b>Electrical Safety Class</b>	: Class I
<b>Net Weight [kg]</b>	: 1.10kg

---

**Certifications/Declarations** : CE/UKCA

---

**Warranty [Y]** : 5 years

---