

Tornado T2

Tornado T2 15W CDL E27 220-240V 1PF

Tornado has outstanding brightness which makes your colors appear more Vivid. It starts instantly (except 5W) and fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

Product data

• General Characteristics

Cap-Base	E27
Bulb	Spiral
Nominal Lifetime	10000 hr
Rated Lifetime	10000 hr
(hours)	
Rated Lifetime	10 an
(years)	

• Light Technical Characteristics

Color Code Color Rendering Index	865 [CCT of 6500K] 81 (min) Ra8
Color Designation (text)	Cool Daylight
Color Temperature	6500 K
Color Temperature	6500 K
Technical	
Luminous flux lamp	900 Lm
Rated Luminous Flux	900 Lm
Luminous Efficacy	61 Lm/W
Lamp	
Lumen Maintenance 2000h	88 %
Lumen Maintenance 6000h	70 %
LLMF - end nominal lifetime	65 %
Chromaticity Coor- dinate X	313 -
Chromaticity Coor- dinate Y	337 -

• Electrical Characteristics

Rated Wattage

15.0 W

Lamp Wattage 15 W Power Factor 0.6 -Voltage 220-240 V Lamp Current mA 110 mA Line Frequency 50/60 Hz Dimmable No Wattage Equivalent Starting Time 70 W 0.3 s Warm-up Time to 5 (min), 40 (max) s 60% Light Outp

Environmental Characteristics

Energy Efficiency A Label (EEL) Mercury (Hg) 1.5 (nom), 2.0 (max) mg Content Energy consumption 15 kWh kWh/1000h

Measuring Conditions

Switching cycle

• Product Dimensions

Overall Length C Diameter D Width F 107.5 (max) mm 51.5 (max) mm 42.5 (max) mm

10000X

• Product Data

Order code Full product code Full product name 929689114802 929689114802 Tornado T2 15W CDL E27 220-240V 1PF



Tornado T2

Order product name	Tornado T2 15W CDL E27 220-240V 1PF/6
Pieces per pack Packing configuration Packs per outerbox Bar code on pack - EAN1	1 6 6 8727900925845

Warnings and Safety

• Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic
 Bar code on outerbox - EAN3
 8727900925852

 Logistic code(s) -12NC
 929689114802

 Net weight per piece
 0.050 kg


bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Compact fluorescent lamps have to be treated as special waste, they
must be taken to your local waste facilities for recycling. The
European Lighting Industry has set up an infrastructure, capable of
recycling mercury, other metals, glass etc.

Dimensional drawing

Product C (Max) D (Max) F (Max)

QSPIR-F Erp 15W/865 E27 220-240V 50/60Hz 107.5 51.5 42.5		0 (1 100)	B (i lust)	1 (11004)
	QSPIR-F Erp 15W/865 E27 220-240V 50/60Hz	107.5	51.5	42.5





E27



© 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting