

# MASTER LEDspot LV

## MASTER LEDspotLV D 7-35W 827 MR16 60D

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot and general lighting applications in the hospitality industry. It is particularly suited to public areas such as receptions, lobbies, corridors, stairwells and washrooms, where the light is on all the time. The robustly designed MASTER LEDspot offers a choice of beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). Innovative active cooling technology - thanks to the fan inside - results in maximum performance of the lamp. The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

#### Product data

#### • General Characteristics

Cap-Base GU5.3

MR16 [MR 16inch/50mm] Bulb

Rated Lifetime 40000 hr

(hours) Rated Lifetime 25 an

(years)

#### • Light Technical Characteristics

Color Code Warm White

Color Designation (text)

60 D Beam Angle

Beam Description 60D [Wide beam] 2700 K

Correlated Color Temperature

Luminous Intensity 420 cd

Color rendering

80 index

Color Temperature 2700 K [CCT 2700K]

Rated Luminous Flux

#### • Electrical Characteristics

7 W Wattage Wattage Technical 7 W 12 V Voltage Power Factor 0.7 -Lamp Current mA 750 mA Dimmable

35 W Wattage Equivalent 0.5 s Starting Time

#### Measuring Conditions

50000x Switching cycle

## • Product Dimensions

Overall Length C 54 mm 50 mm Diameter D

## • Product Data

Order code 929000237902 929000237902 Full product code

Full product name MASTER LEDspotLV D 7-35W 827

MR16 60D

Order product name MAS LEDspotLV D 7-35W 827 MR16

60D Pieces per pack 10 Packing configuration 10

Packs per outerbox

Bar code on pack -EAN1

Bar code on

outerbox - EAN3

Logistic code(s) -

12NC

Net weight per piece

8718291655442

8718291655459

929000237902

0.060 kg






## Warnings and Safety

- $\bullet$  Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)


• Not intended for use with emergency light fixtures or exit lights

# Dimensional drawing



#### MASTER LEDspotLV D 7-35W 827 MR16 60D

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED D 7-50W 2700K MR16 60D	54	-	50	-



GU5.3



© 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.