

# MASTER PL-S 2 Pin

# MASTER PL-S 7W/830/2P 1CT

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

## Product data

#### General Characteristics

Cap-Base	G23 [Two-Pin Compact Fluorescent; low preheat current; two retainers]
Cap-Base Information	2P
Life to 10% failures EM	6500 hr
Life to 50% failures	10000 hr
EM	
LSF EM 2000h Rated,	99 %
3h cycle	
LSF EM 4000h Rated,	98 %
3h cycle	
LSF EM 6000h Rated,	95 %
3h cycle	
LSF EM 8000h Rated,	86 %
3h cycle	

#### • Light Technical Characteristics

Color Code	830 [CCT of 3000K] 82 Ra8
Color Rendering Index	02 Nd0
Color Designation	Warm White
(text)	
Color Temperature	3000 K
Luminous Flux EM	405 Lm
25°C, Rated	
Luminous Flux EM	400 Lm
25°C, Nominal	
Lum Efficacy Rated	57 Lm/W
EM 25°C	
LLMF EM 2000h	94 %
Rated	
LLMF EM 4000h	91 %
Rated	
LLMF EM 6000h	89 %
Rated	



LLMF EM 8000h	86 %
Rated	
Design Temperature	28 C
Chromaticity Coor-	435 -
dinate X	
Chromaticity Coor-	401 -
dinate Y	

#### • Electrical Characteristics

Lamp Wattage	7 W
Lamp Wattage EM	7 W
25°C, Nominal	
Lamp Wattage EM	7.1 W
25°C, Rated	
Lamp Voltage EM	47 V
25°Ċ	
Lamp Current EM	0.175 A
25°Ċ	
Dimmable	No

#### • Environmental Characteristics

Energy Efficiency	В
Label (EEL)	
Mercury (Hg)	1.4 mg
Content	
Energy consumption	9 kWh
kWh/1000h	

#### • Product Dimensions

Base Face to Base
Face A
Insertion Length B
Overall Length C
Diameter D

113 (max) mm 135 (max) mm 28 (max) mm

97 (max) mm



# MASTER PL-S 2 Pin

Diameter D1
Product Data
Order code
927935683011

Full product code 92 Full product name M Order product name M 50 Pieces per pack 1 Packing configuration 50 Packs per outerbox 50


927935683011 MASTER PL-S 7W/830/2P 1CT MASTER PL-S 7W/830/2P 1CT/ 5X10BOX 1 5X10CC 50

Bar code on pack - EAN1	8711500260628
Bar code on inter- mediate packing -	8711500260635
EAN2	
Bar code on	8711500260642
outerbox - EAN3	
Logistic code(s) -	927935683011
12NC	
ILCOS code	FSD-7/30/1B-I-G23
Net weight per piece	26.000 gr

• Dimming is not possible


- Warnings and Safety
- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position

## Dimensional drawing




#### MASTER PL-S 7W/830/2P 1CT

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
PL-S 7W/830/2P LM	97	113	135	28	13



G23

## Photometric data





© 2013 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting