

MASTERCcolour CDM-TP

MASTERCcolour CDM-TP 70W/830 PG12-2 1CT

Range of protected, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light to be used in open luminaires



Product data

• General Characteristics

Cap-Base	PG12-2
Bulb	T31 [T 31mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 5% failures	9000 hr
Life to 20% failures	13000 hr
Life to 50% failures	16000 hr

• Light Technical Characteristics

Color Code	830 [CCT of 3000K]
Color Rendering Index	80 Ra8
Color Designation (text)	Warm White
Color Temperature	3000 K
Color Temperature Technical	3100 K
Luminous Flux Lamp EM	6000 Lm
Luminous Efficacy Lamp EM	82 Lm/W
Lumen Maintenance EM 2000h	80 %
Lumen Maintenance EL 2000h	80 %
Lumen Maintenance EM 5000h	70 %
Lumen Maintenance EL 5000h	70 %
Lumen Maintenance EM 10000h	60 %
Lumen Maintenance EL 10000h	65 %
Lumen Maintenance EM 15000h	50 %
Lumen Maintenance EL 15000h	

Lumen Maintenance EL 15000h	60 %
Chromaticity Coordinate X	428 -
Chromaticity Coordinate Y	401 -

• Electrical Characteristics

System Power EM	88 W
System Power EL	83 W
Lamp Wattage	70 W
Lamp Wattage EM 25°C, Nominal	70.0 W
Lamp Wattage EM 25°C, Rated	73.0 W
Lamp Voltage	90 V
Lamp Current EM	0.98 A
Ignition Time	30 (max) s
Run-up time 90%	3 (max) min
Re-ignition Time [min]	15 (max) min
Dimmable	No

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	5.2 mg
Energy consumption kWh/1000h	80 kWh

• UV-related Characteristics

Damage Factor D/fc PET (NIOSH)	0.3 (max) - 8 (min) h500lx
--------------------------------	----------------------------

PHILIPS

• Luminaire Design Requirements

Cap-Base Temperature	210 (max) C
Bulb Temperature	400 (max) C

• Product Dimensions

Overall Length C	149 (max) mm
Diameter D	32.00 (max) mm
Light Center Length L	91 mm
Arc Length O	7 mm

• Product Data

Order code	928086909230
------------	--------------


Full product code	928086909230
Full product name	MASTERColour CDM-TP 70W/830 PG12-2 1CT
Order product name	MASTERC CDM-TP 70W/830 PG12-2 1CT/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500201270
Bar code on outerbox - EAN3	8711500201287
Logistic code(s) - 12NC	928086909230
ILCOS code	MTS/UB-70/830-H-PG12-2-32/149
Net weight per piece	0.073 kg

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear


- Control gear must include end-of-life protection (IEC61167, IEC 62035)

Dimensional drawing




MASTERColour CDM-TP 70W/830 PG12-2 1CT

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	O (Min)	O (Norm)	O (Max)
CDM-TP 70W/830 PG12-2	149	32.00	89	91	93	-	7	-



PG12-2

Photometric data



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, October 9
data subject to change