

EXC for SOX

EXC 66 SOX-E 220-240V 50/60Hz

Electronic drivers for SOX lamps; designed to save energy and reduce maintenance costs

Product data

• General Characteristics

Application code	E11
Rated Lamptype	SOX-E
Rated Number of Lamps	1 piece
Rated Ballast-Lamp Power	66
Line Voltage	220-240 V
Line Current	0.30 A
Line Frequency	50/60 Hz
Housing	L 280x39x28
IP Classification	20
Luminaires	
Lifetime 90% surv.@Tcaselife	50000 hr

• Operating Characteristics

Automatic restart	No
Ignition switch-off time	0.08 min
Ignition Voltage	0.5 (min), 1.0 (max) kV
Operating frequency *	45 kHz
Mains voltage safety (AC)	-10%/+10%
Mains voltage performance (AC)	-8%/+6%
Min. Mains voltage operational	180 (min) V
Output peak voltage	1000 (max) V
Inrush current Peak	40 (max) A
Inrush current Width	0.15 ms
Earth leakage current	0.5 mA
Lamp Power Tolerance	-10%/+10%

PowerFactor 100% output power	0.95 -
Overvoltage protection 320Vac	48 hr
Overvoltage protection 350Vac	2 hr
Max ballast on MCB(16A type B)	22 x
Hum and Noise level	37 dB(A)

• Wiring Characteristics

Cable-Cap output-wires mutual	1000 pF
Connector type	Insert
Max. cable length Device/Lamp	10 m
Striplength	8.0 mm
Wcs Ballast contacts	0.50-2.50 mm ²

• System Chars on driver level

Rated Lamp Power on SOX-E	66
System Power on SOX-E	73.0
Lamp Power on SOX-E	67.0
Power Loss on SOX-E	6.0

• Temperature Characteristics

T-case life	75 C
T-case switch-off	75 (min) C
T-ambient	-20 (min), 50 (max) C
T-storage	-40 (min), 80 (max) C

PHILIPS

• Product Dimensions

Length A1	280.0 mm
Fixing Hole Distance	265.0 mm
Length A2	
Width B1	40.0 mm
Height C1	28.0 mm
Fixing Hole Diameter	4.2 mm
D1	

• Approval & Application Chars


EMI 9 kHz ... 300MHz	CISPR 15 ed 7.1
Safety Standard	EN 60928, 60926
Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001
Harmonic current emissions	EN 60555.2
Vibrations	IEC 68-2-6 Fc
Bumps	IEC 68-2-29 Eb
Humidity	IEC 928-13

Approval marks	ENEC
CE marking	Yes
ENEC certificate	Yes
VDE certificate	No
VDE-EMV certificate	No
CB Certificate	Yes

• Product Data

Order code	913700621766
Full product code	913700621766
Full product name	EXC 66 SOX-E 220-240V 50/60Hz
Order product name	EXC 66 SOX-E 220-240V 50/60Hz
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	8711500062444
Bar code on outerbox - EAN3	8711500062451
Logistic code(s) - 12NC	913700621766
Net weight per piece	0.275 kg

Dimensional drawing



EXC 66 SOX-E 220-240V 50/60Hz

Product	A1 (Norm)	A2 (Norm)	B1 (Norm)	C1 (Norm)	D1 (Norm)
EXC 66 SOX-E 220-240V 50/60Hz	280.0	265.0	40.0	28.0	4.2



© 2015 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, July 15
data subject to change