



MASTER PL-R Eco 4 Pin

MASTER PL-R Eco 17W/840/4P 1CT

Energy-saving compact fluorescent lamp Compact long-arc low-pressure mercury discharge lamp Envelope consists of six parallel narrow fluorescent tubes

Product data

• Product Data

Order code	266040 70
Full product code	871150026604070
Full product name	MASTER PL-R Eco 17W/840/4P 1CT
Order product name	MASTER PL-R Eco 17W/840/4P 1CT/ 5X10BOX
Pieces per pack	1
Packing configuration	5X10CC
Packs per outerbox	50
Bar code on pack - EAN1	8711500266040
Bar code on intermediate packing - EAN2	8711500266057
Bar code on outerbox - EAN3	8711500266064
Logistic code(s) - 12NC	927910084050
ILCOS code	FSM6H-17/40/1B-L/P-GR14q=1
Net weight per piece	83.000 gr

• General Characteristics

Cap-Base	GR14q-1
Cap-Base Information	4P
Life to 50% fail Preheat EL,3h	24000 hr
Life to 50% fail Nonpreh EL,3h	12000 hr
Life to 10% fail Nonpreh EL,3h	10000 hr
Life to 10% fail Preheat EL,3h	19000 hr
LSF HF Preheat 20000h Rated,3h	87 %
LSF HF Preheat 12000h Rated,3h	97 %

LSF HF Preheat 8000h Rated,3h	98 %
LSF HF Preheat 6000h Rated,3h	99 %
LSF HF Preheat 4000h Rated,3h	99 %
LSF HF Preheat 2000h Rated,3h	99 %
LSF HF Preheat 16000h Rated,3h	94 %

• Electrical Characteristics

Lamp Wattage	17 W
Dimmable	yes
Lamp Wattage EL 35°C base up	18 W
Lamp Voltage EL 25°C base up	120 V
Lamp Current EL 25°C base up	0.150 A
Wattage EL 25°C base up, Rated	17.8 W
Wattage EL 25°C base up, Nom.	17 W

• Environmental Characteristics

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content	1.4 mg

• Light Technical Characteristics

Colour Code	840 [CCT of 4000K]
-------------	--------------------



asimpleswitch.com

PHILIPS

sense and simplicity

MASTER PL-R Eco 4 Pin


Colour Rendering Index	82 Ra8
Colour Designation	Cool White
Colour Temperature	4000 K
Chromaticity Coordinate X	387 -
Chromaticity Coordinate Y	389 -
Luminous Flux EL 35°C base up	1500 Lm
Lum Efficacy Rated HF 25°C	70 Lm/W
LLMF HF 20000h Rated	89 %
LLMF HF 16000h Rated	90 %
LLMF HF 12000h Rated	91 %
LLMF HF 8000h Rated	92 %

LLMF HF 6000h Rated	93 %
LLMF HF 4000h Rated	94 %
LLMF HF 2000h Rated	96 %
Lum Flux Rated HF 25°C,base up	1250 Lm
Design Temperature	35 C
Lum Flux Nom. HF 25°C,base up	1250 Lm



• Product Dimensions

Base Face to Base Face A	121.7 mm
Insertion Length B	142.0 mm
Overall Length C	148.6 mm
Diameter D	41.0 mm



Dimensional drawing



Product	A (Max)	B (Max)	C (Max)	D (Max)
PL-R 17W/840/4P	121.7	142.0	148.6	41.0



Photometric data



Lamps being part of this product family comply with Commission Regulation (EC) No 245/2009 – Ecodesign requirements, applicable from 13 April 2010.

1.3 Product information requirements on lamps

- a) Nominal and rated lamp wattage;
 - b) Nominal and rated lamp luminous flux;
 - c) Rated lamp efficacy at 100 h in standard conditions (25 °C, for T5 lamps at 35 °C). For fluorescent lamps both at 50 Hz (mains frequency) operation (where applicable) and at High Frequency (> 50 Hz) operation (where applicable) for the same rated luminous flux in all cases, indicating for High Frequency operation the calibration current of the test conditions and/or the rated voltage of the HF generator with the resistance. It shall be stated in a conspicuous manner that the power dissipated by auxiliary equipment such as ballasts is not included in the power consumed by the source;
 - d) Rated lamp Lumen Maintenance Factor at 2000 h, 4000 h, 6000 h, 8000 h, 12000 h, 16000 h and 20000 h (up to 8000 h only for new lamps on the market where no data is yet available), indicating which operation mode of the lamp was used for the test if both 50 Hz and High Frequency operation are possible;
 - e) Rated lamp Survival Factor at 2000 h, 4000 h, 6000 h, 8000 h, 12000 h, 16000 h and 20000 h (up to 8000 h only for new lamps on the market where no data is yet available), indicating which operation mode of the lamp was used for the test if both 50 Hz and High Frequency operation are possible;
 - f) Lamp mercury content as X.X mg;
 - g) Colour Rendering Index (Ra) of the lamp;
 - h) Colour temperature of the lamp;
 - i) Ambient temperature inside the luminaire at which the lamp was designed to maximise its luminous flux. If this temperature is equal to or lower than 0 °C or equal to or higher than 50 °C it shall be stated that the lamp is not suitable for indoor use at standard room temperatures;
 - j) For fluorescent lamps without integrated ballast, the energy efficiency index(es) of ballasts as defined in Table 17 with which the lamp can operate.
- See Table 17-EuP245.pdf for Table 17 – Energy efficiency index requirements for non-dimmable ballasts for fluorescent lamps.
For more information see: <http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2009:076:0017:0044:EN:PDF>



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, March 18
data subject to change