

MASTER LEDspot MV

MAS LEDspotMV VLE D 4.3-50W GU10 827 25D

Delivering a warm, halogen-like accent beam, MASTER LEDspot MV is a perfect fit for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suitable to public areas where the light is on 24/7, such as lobbies, corridors, stairwells.MASTER LEDspot MV delivers huge energy savings and minimizes maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. These LEDspots are compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement for halogen or incandescent spots. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

Product data

• General Information

 Cap-Base
 GU10 [GU10]

 Nominal Lifetime (Nom)
 35000 h

 Switching Cycle Technical Type
 50000X

 4.3-50W

• Light Technical

827 [CCT of 2700K] Color Code Beam Angle (Nom) Light Distribution 25D [Medium beam] Luminous Flux 380 lm (Nom) Luminous Flux 380 lm (Rated) (Nom) Luminous Intensity 1400 cd (Nom) Color Designation Warm White (WW) Rated Beam Angle 25° 2700 K Correlated Color Temperature (Nom) Luminous Efficacy 82.56 lm/W (rated) (Nom) Color Consistency 6 steps Color Rendering Index (Nom) LLMF At End Of 70 % Nominal Lifetime (Nom) Luminous Flux In 90° 355 lm Cone (Rated)

• Operating and Electrical

50-60 Hz Input Frequency Power (Rated) 4.3 W (Nom) Lamp Current (Nom) 23 mA Wattage Equivalent 50 W Starting Time (Max) 0.5 s instant full light Warm Up Time To 60% Light (Nom) Power Factor (Nom) Voltage (Nom) 220-240 V

• Temperature

T-Case Maximum 83 °C (Nom)

• Controls and Dimming

Dimmable Yes

Approval and Application

Suitable For Accent Yes
Lighting
Energy Efficiency A++
Label (EEL)
Energy Consumption kWh/1000 h



MASTER LEDspot MV

• Product Data

Full product code 871869643838100

MAS LEDspotMV VLE D 4.3-50W Order product name

GU10 827 25D 8718696438381

EAN/UPC - Product 929001130102 Order code

Warnings and Safety


 \bullet Operating temperature range is between -20 $^{\circ}$ C and 45 $^{\circ}$ C ambient

1 Numerator - Quantity Per Pack Numerator - Packs 10

per outer box . Material Nr. (12NC) 929001130102 Net Weight (Piece) 0.036 kg

- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights


Dimensional drawing




3.5-35W, 4-35W, 4.3-50W, 4.5-50W, 5.4-50W, 5.5-50W, 6-50W GU10

LED VLE D 4.3-50W GU10 827 25D

Product	D	С
MAS LEDspotMV VLE D 4.3-50W GU10 827 25D	50 mm	55 mm



Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.