

HF-Matchbox Blue

HF-M BLUE 114 LH TL/PL-S/PL-C 230-240V

HF-Matchbox Blue is an affordable, reliable, compact, lightweight and high-frequency ballast for use with system wattages below 25 W in combination with TL mini, TL-D, TL5 and TL5c, PL-T/C, and PL-L/S lamps.The HF-M Blue range has a robust design, meets all relevant international safety and performance standards and has an energy efficiency index (CELMA EEI) of A2.

Product data

General Information

Lamp TypeTL/PL-S/PL-CNumber Of Lamps1 piece/unitNumber Of Products101On MCB (16A TypeB) (Nom)Automatic RestartYes

• Operating and Electrical

Input Voltage 230 to 240 V Input Frequency 50-60 1 Hz Power Factor 100% 0.64 Load (Nom) Ignition Time (Max) 0.5 s -8%-+6% Mains Voltage Performance (AC) -10%-+10% Mains Voltage Safety (AC) 2.9 W Power Losses (Nom)

• Wiring

Connector Type Input Terminals	Insert
Color Input Termi- nals	Grey
Color Output Termi- nals	Grey
Connector Type Output Terminals	Insert
Cable Length From Device To Lamp	1.50 m
Cable Length Hot Wiring	0.30 m
Wire Striplength	8.0-9.0 mm

Input Terminal Cross Section	0.50-1.50 mm ²
Output Terminal Cross Section	0.50-1.50 mm ²
• System characteristics	
Rated Ballast-Lamp Power	14 W
System Power On PL-S	14.1 W
Rated Lamp Power On PL-S	14 W
Power Loss On PL-S	2.2 W
Lamp Power On PL-S	11.9 W
System Power On PL-C	14.6 W
Rated Lamp Power On PL-C	14 W
Power Loss On PL-C	2.4 W
Lamp Power On PL- C	12.2 W
Lamp Power On TL	11.8 W
Rated Lamp Power On TL	14 W
System Power On TL	15.7 W
Temperature	

T-Ambient (Max)	40 °C
T-Ambient (Min)	-10 °C
T-Case Maximum	75 °C
(Max)	

LH

Mechanical and Housing

Housing



• Emergency Operation

Battery Voltage Lamp 194-254 V Ignition

• Approval and Application

Approval Marks

F-Marking CE marking VDE certificate CB Certificate

• Product Data

Full product code Order product name EAN/UPC - Product Order code Numerator - Quantity Per Pack Numerator - Packs per outer box Material Nr. (12NC)

Net Weight (Piece)

871150053682230 HF-M BLUE 114 LH TL/PL-S/PL-C 230-240V 8711500536822 913700421766 1

913700421766 0.036 kg

50



 $\ensuremath{\mathbb{C}}$ 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting