

HF-Matchbox Blue

HF-M BLUE 121 LH TL5 230-240V

HF-Matchbox Blue is an affordable, reliable, compact, lightweight and high-frequency ballast for use with system wattages below 25 W in combination with TL mini, TL-D, TL5 and TL5c, PL-T/C, and PL-L/S lamps. The HF-M Blue range has a robust design, meets all relevant international safety and performance standards and has an energy efficiency index (CELMA EEI) of A2.

Product data

• General Information

Lamp Type TL5 Number Of Lamps 1 piece/unit Number Of Products 59 On MCB (16A Type B) (Nom)

Yes

Operating and Electrical

Automatic Restart

Input Voltage 230 to 240 V Input Frequency 50-60 1 Hz Power Factor 100% 0.64 Load (Nom) Ignition Time (Max) 0.5 sMains Voltage -8%-+6% Performance (AC) -10%-+10% Mains Voltage Safety (AC) Power Losses (Nom) 2.4 W

Wiring

Connector Type Insert Input Terminals Color Input Termi-Grey nals Grey Color Output Terminals Connector Type Insert Output Terminals 1.50 m Cable Length From Device To Lamp 0.30 m Cable Length Hot Wiring Wire Striplength 8.0-9.0 mm Input Terminal Cross 0.50-1.50 mm²
Section
Output Terminal 0.50-1.50 mm²
Cross Section

• System characteristics

Rated Ballast-Lamp 21 W Power

• Temperature

T-Ambient (Max) 40 °C T-Ambient (Min) -10 °C T-Case Maximum 75 °C (Max)

Mechanical and Housing

Housing LH

• Emergency Operation

Battery Voltage Lamp 194-254 V Ignition

Approval and Application

Approval Marks F-Marking
CE marking
VDE certificate
CB Certificate

• Product Data

Full product code 871150053646430
Order product name HF-M BLUE 121 LH TL5 230-240V



HF-Matchbox Blue

EAN/UPC - Product Order code Numerator - Quantity Per Pack

8711500536464 913700418366

Numerator - Packs

per outer box Material Nr. (12NC) Net Weight (Piece)

913700418366 0.043 kg

50



© 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.