

HF-Matchbox Red

HF-M RED 109 SH TL/PL-S 230-240V

HF-Matchbox Red is an affordable, reliable, compact, lightweight and high-frequency ballast for use with system wattages below 25 W in combination with TL mini, TL-D, TL5 and TL5c, PL-T/C, and PL-L/S lamps. The HF-M Red range has a robust design, meets all relevant international safety and performance standards and has an energy efficiency index (CELMA EEI) of A2.

Product data

• General Information

Lamp Type TL/PL-S
Number Of Lamps 1 piece/unit
Number Of Products 159
On MCB (16A Type
B) (Nom)
Automatic Restart Yes

· Operating and Electrical

Input Voltage 230 to 240 V Input Frequency 50-60 1 Hz Power Factor 100% 0.64 Load (Nom) Ignition Time (Max) 0.45 sMains Voltage -8%-+6% Performance (AC) -10%-+10% Mains Voltage Safety (AC) Power Losses (Nom) 1.7 W

Wiring

Connector Type Insert Input Terminals Color Input Termi-Black nals Grey Color Output Terminals Connector Type Insert Output Terminals Cable Length From 1.50 m Device To Lamp 0.30 m Cable Length Hot Wiring Wire Striplength 8.0-9.0 mm Input Terminal Cross 0.50-1.50 mm² Section
Output Terminal 0.50-1.50 mm² Cross Section

System characteristics

Rated Ballast-Lamp 9 W Power System Power On 8.2 W PĹ-S Rated Lamp Power 9 W On PL-S 1.7 W Power Loss On PL-S Lamp Power On PL-S 6.5 W Lamp Power On TL 5.3 W Rated Lamp Power 9 W On TL System Power On TL 7 W

• Temperature

T-Ambient (Max) 40 °C T-Ambient (Min) -10 °C T-Case Maximum 75 °C (Max)

• Mechanical and Housing

Housing SH

• Emergency Operation

Battery Voltage Lamp 194-254 V Ignition



HF-Matchbox Red

• Approval and Application

Approval Marks F-Marking

CE marking ENEC certificate **CB** Certificate

• Product Data

Full product code 871150093142930 Order product name EAN/UPC - Product Order code Numerator - Quantity Per Pack Numerator - Packs

50


HF-M RED 109 SH TL/PL-S 230-240V

8711500931429

913700422866

per outer box Material Nr. (12NC) 913700422866 Net Weight (Piece) 0.034 kg

Dimensional drawing



HF-M RED 109 SH TL/PL-S 230-240V







© 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.