



Halogen reflector

13158 150W GX5.3 21V 1CT

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data


General Information		Voltage (Nom)	
Cap base	GX5.3 [GX5.3]	21 V	
Philips code	13158	Controls and Dimming	
ANSI Code	ELD-EJN	Dimmable	Yes
LIF Code	-	Mechanical and Housing	
Operating position	S90 [Standing +/-90D or Base Down (BDH)]	Cap-base information	na [-]
Main application	Projection	Bulb material	Quartz-UV Open
Life to 50% failures (nom.)	40 h	Reflector finish	Stippled
J code	-	Filament shape	-
Light Technical		Filament dimensions WxH	-
Luminous flux (rated) (nom.)	320 lm	Luminaire Design Requirements	
Colour rendering index (nom.)	100	Bulb temperature (max.)	900 °C
Operating and Electrical		Pinch temperature (max.)	400 °C
Power (Rated) (Nom)	150 W		

Halogen reflector

Working distance WD	165 mm
Product Data	
Full product code	871150041060330
Order product name	ELD 150W 21V 24PK
EAN/UPC – product	8711500410603
Order code	41060330

Numerator – quantity per pack	1
SAP numerator – packs per outer box	24
Material no. (12 NC)	923921319894
SAP net weight (piece)	0.023 kg

Dimensional drawing



13158 150W GX5.3 21V

Product

ELD 150W 21V 24PK

