

Halogen non-reflector

7787LL 400W G6.35 36V 1CT

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data

General Characteristics

Philips Code	7787LL
ANSI Code	-
LIF Code	-
Cap-Base	G6.35
Bulb Material	Quartz-UV Open
Filament Shape	Flat
Operating Position	s90
Main Application	Projection
Life to 50% failures	300 hr

• Light Technical Characteristics

Color Rendering Index	100 Ra8			
Color Temperature Technical	3350 K			
Luminous Flux Lamp	12200 Lm			

• Electrical Characteristics

Lamp Wattage	400 W
Voltage	36 V

• Luminaire Design Requirements

Pinch Temperature	350 (max) C
Bulb Temperature	900 (max) C

Product Dimensions


Diameter D Light Center Length L Pin Diameter P Filament Dimensions (WxH) [mm] 18 (max) mm 35.75 (min), 36 (nom), 36.25 (max) mm 0.95 (min), 1 (nom), 1.05 (max) mm 9.4x4.7

• Product Data

Order code Full product code Full product name Order product name Pieces per pack Packing configuration Packs per outerbox Bar code on pack -EAN1 Bar code on intermediate packing -EAN2 Bar code on outerbox - EAN3 Logistic code(s) -12NC Net weight per piece 924031523306 924031523306 7787LL 400W G6.35 36V 1CT 7787LL 400W G6.35 36V 1CT/3X8F 1 3X8F 24 8711500506559 8711500420411 8711500422965 924031523306 0.008 kg



Dimensional drawing



7787LL 400W G6.35 36V 1CT

Product	C (Norm)	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	P (Min)	P (Norm)	P (Max)
7787LL 400W G6.35 36V	-	-	18	35.75	36	36.25	0.95	1	1.05





G6.35



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting