



Blue (/52) TL/TL-D

TL 20W/52 SLV/25

By emitting light almost entirely within the 400 to 500 nm bandwidth and peaking at 450 nm, Philips TL/TL-D color 52 lamps have no radiation from the short wave UVB waveband. They are therefore suitable to be used in systems for applications such as Agriculture and Neonatal Jaundice Phototherapy

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take them to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Photobiological safety – IEC 62471 – Risk Group 2. CAUTION – Possibly hazardous optical radiation emitted from these products.

Product data


General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	-
Life to 50% Failures (Nom)	9000 h
Useful Life (Nom)	2000 h
Light Technical	
Color Code	52
Luminous Flux (Nom)	318 lm
Beam Description	-
Chromaticity Coordinate X (Nom)	154
Chromaticity Coordinate Y (Nom)	69
LLMF 2000 h Rated	20 %
Operating and Electrical	
Power (Nom)	19.3 W
Lamp Current (Nom)	0.36 A

Voltage (Nom)	59 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	T38 [T 38mm]
Approval and Application	
Mercury (Hg) Content (Nom)	8.0 mg
Product Data	
Full product code	871150064302540
Order product name	TL 20W/52 SLV/25
EAN/UPC - Product	8711500643025
Order code	928003505203
Numerator - Quantity Per Pack	1

Blue (/52) TL/TL-D

Numerator - Packs per outer box	25
Material Nr. (12NC)	928003505203
Net Weight (Piece)	156.000 g

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 20W/52 SLV/25	40.5 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

Photometric data

