

## QTP5 2X14...35

QUICKTRONIC PROFESSIONAL 5 | ECG for FL 16 mm



### Areas of application

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Modernization of existing systems
- Suitable for luminaires of protection classes I and II

### Product family benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Perfect lamp start for applications with motion sensors
- Automatic restart after lamp replacement
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

### Product family features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating
- Lifetime: up to 100,000 h (temperature at  $T_c = 65$  °C, max. 10 % failure rate)
- Energy Efficiency Index EEI: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Safety: to EN 61347-2-3
- Lamp operation: to EN 60929

# Product datasheet

## Technical data

### Electrical data

Input voltage AC	198...264 V
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage DC	176...276 V
Operating frequency	40...50 kHz
Max. ECG no. on circuit breaker 10 A (B)	12 <sup>1)</sup>
Max. ECG no. on circuit breaker 16 A (B)	19 <sup>1)</sup>
Inrush current	24 A


<sup>1)</sup> Type B

### Light technical data

Starting time	1.0 s <sup>1)</sup>
---------------	---------------------

<sup>1)</sup> If there is a temporary interruption in the power supply (< 0.5 s), the lamp will start within 0.3 s

### Dimensions & weight



Length	360.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	350.0 mm
Product weight	234.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Permitted rel. humidity during operation	5...85 %

### Lifespan

## Product datasheet

<b>ECG lifetime</b>	100000 h <sup>1)</sup>
---------------------	------------------------

<sup>1)</sup> At  $T_{case} = 65^{\circ}\text{C}$  at  $T_c$  point / 10% failure rate

### Expected Lifetime

Product name	Lamp group				
QTP5 2X14...35	HE 35 W	ECG ambient temperature [ta]	40	50	60
		Temperature at tc-point [°C]	55	65	70
		Lifetime [h]	100000	100000	60000

### Capabilities

<b>Suitable for fixtures with prot. class</b>	I / II
<b>End of lamp life safety shutdown</b>	EOL T.2

### Certificates & standards

<b>Approval marks – approval</b>	VDE / VDE-EMC / CE / ENEC 10
<b>EEL – Energy Label</b>	A2 BAT
<b>Standards</b>	Acc. to EN 61347-2-3/Acc. to EN 60929/Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547
<b>Protection class</b>	III
<b>Type of protection</b>	IP20


### Logistical data

<b>Commodity code</b>	850410809000
-----------------------	--------------

## Product datasheet

### Wiring Diagram

---













---

### Wiring diagram








---

### Download Data

File	
	Product Datasheet 334048_QUICKTRONIC PROFESSIONAL &#150; QTP5
	Product Datasheet 502688_ECG lifetime - QUICKTRONIC non DIM
	Product Family Datasheet 336478_Family data sheet QTP5
	Certificates 335002_EMC-Marks approval
	Certificates 335097_INOTEC
	Certificates 335098_CEAG
	Certificates 335101_ENEC-VDE-Marks approval
	Certificates 335128_VDE Quality Tested Simplified luminaire approbation
	Certificates 335169_Manufacturer's declaration &#150; LampECG combinations: Frequent switching
	Certificates 592319_EAC certificate for Quicktronics QT

## Product datasheet

---

	Certificates 504210_VDE-EMC-Certificate QT5
	Declarations of conformity 334802_CE conformity
	Installation/Operation notice 334142_Technical guide - ECGs for T5-lamps
	CAD data 3-dim 313485_360x30x21 9900024
	CAD data 3-dim 313490_360x30x21 9900024
	CAD data 3-dim 314282_360x30x21 9900024
	CAD data PDF 313392_360x30x21 9900024

---

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321329073	QTP5 2X14...35	Shipping carton box 20	370 mm x 96 mm x 170 mm	6.04 dm <sup>3</sup>	4900.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

## QTP5 2X14...35

QUICKTRONIC PROFESSIONAL 5 | ECG for FL 16 mm

Product name	Lamp group	Nominal current	Nominal wattage + Power loss	Luminous flux at 35 °C	Number of lighting outlets
QTP5 2X14...35	DULUX L 26 W HE	0.26 A	57.00 W	2470 lm	2
	DULUX L 28 W HE	0.26 A	56.00 W	2525 lm	2
	HE 13 W ES	0.13 A	28.00 W	1350 lm	2
	HE 14 W	0.14 A	30.00 W	1200 lm	2
	HE 19 W ES	0.185 A	42.00 W	1800 lm	2
	HE 21 W	0.20 A	45.00 W	1900 lm	2
	HE 25 W ES	0.24 A	54.00 W	2450 lm	2
	HE 28 W	0.26 A	60.00 W	2600 lm	2
	HE 32 W ES	0.30 A	68.00 W	3100 lm	2
	HE 35 W	0.33 A	75.00 W	3300 lm	2
HE 35 W XT	0.33 A	75.00 W	3300 lm	2	