# Product data sheet Characteristics

# A9A15218

modular safety transfomer iTR - 230 V 50..60 Hz - output 12..24 V - 16 VA



#### Main

Man	
Transformer type	Safety transformer
Range	Acti 9
Range of product	Acti 9
Product name	Acti 9 iTR
Product or component type	Transformer
Device short name	ITR

## Complementary

Complementary		
[Ue] rated operational voltage	230 V AC 50/60 Hz	
Output voltage	12/24 V : +/-5 % on load 14/28 V : off load	Parental and the second se
Output short-circuit protection	Built-in	<u>:</u>
Rated power in VA	16 VA	<u> </u>
Mounting mode	Fixed	
Mounting support	35 mm symmetrical DIN rail	
9 mm pitches	10	
Height	89 mm	
Width	90 mm	<u> </u>
Depth	60 mm	
Colour	White	
Auxiliary connection terminal	Tunnel type terminals <= 4 mm²	

### Environment

Standards	EN 60742 EN 61558-2-6 IEC 61558-2-6	not intende
Product certifications	NF	<u>.</u>
Overvoltage category	Class II with terminal shields in option	<u></u>
Ambient air temperature for operation	-2055 °C	
Ambient air temperature for storage	-2580 °C	

#### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Contractual warranty	
Warranty period	18 months