



MASTER TL5 High Efficiency

MASTER TL5 HE 21W/827 1SL

This TL5 lamp (tube diameter 16 mm) has a high luminous efficacy, resulting in low energy consumption. The High Efficiency TL5 lamp offers excellent lumen maintenance and good color rendering. Application areas are offices, industry, public and governmental buildings, schools, hospitals and indoor sports lighting.

Product data

• General Characteristics

System Description	High Efficiency
Cap-Base	G5
Cap-Base Information	Green Plate
Bulb	T5 [16 mm]
Life to 50% fail	24000 hr
Preheat EL,3h	
Life to 10% fail	19000 hr
Preheat EL,3h	
LSF HF Preheat	84 %
20000h Rated,3h	
LSF HF Preheat	97 %
16000h Rated,3h	
LSF HF Preheat	99 %
12000h Rated,3h	
LSF HF Preheat	99 %
8000h Rated,3h	
LSF HF Preheat	99 %
6000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	99 %
2000h Rated,3h	

• Light Technical Characteristics

Color Code	827 [CCT of 2700K]
Color Rendering Index	85 Ra8
Color Designation (text)	Incandescent White
Color Temperature	2700 K
Chromaticity Coordinate X	463 -
Chromaticity Coordinate Y	420 -

Luminous Flux Lamp EL 35°C	2100 Lm
Lum Efficacy Rated HF 25°C	93 Lm/W
Lum Efficacy Rated HF 35°C	101 Lm/W
LLMF HF 20000h Rated	90 %
LLMF HF 16000h Rated	91 %
LLMF HF 12000h Rated	92 %
LLMF HF 8000h Rated	93 %
LLMF HF 6000h Rated	94 %
LLMF HF 4000h Rated	95 %
LLMF HF 2000h Rated	96 %
Luminous Flux EL 25°C, Rated	1925 Lm
Luminous Flux EL 25°C, Nominal	1925 Lm
Design Temperature	35 C

• Electrical Characteristics

Lamp Wattage	21 W
Lamp Voltage EL 25°C	126 V
Lamp Current EL 25°C	0.165 A
Dimmable	Yes
Lamp Wattage EL 35°C	20.7 W



MASTER TL5 High Efficiency

Lamp Current EL 35°C	0.170 A
Lamp Voltage EL 35°C	123 V
Lamp Wattage EL 25°C, Rated	20.6 W
Lamp Wattage EL 25°C, Nominal	21 W

• Environmental Characteristics

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content	1.4 mg

• Measuring Conditions

Calibration Current	0.170 A
HF Generator Rated Voltage	246 V
Resistor	725 ohm

• Product Dimensions


Base Face to Base Face A	849.0 (max) mm
-----------------------------	----------------

Insertion Length B	853.7 (min), 856.1 (max) mm
Overall Length C	863.2 (max) mm
Diameter D	17 (max) mm

• Product Data


Order code	927926282755
Full product code	927926282755
Full product name	MASTER TL5 HE 21W/827 1SL
Order product name	MASTER TL5 HE 21W/827 1SL/40
Pieces per pack	1
Packing configuration	40
Packs per outerbox	40
Bar code on pack - EAN1	8711500643209
Bar code on outerbox - EAN3	8711500867537
Logistic code(s) - 12NC	927926282755
ILCOS code	FDH-21/27/1B-L/P-G5-16/850
Net weight per piece	80.500 gr

Dimensional drawing





G5, T5

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL5 21W/827/GP HE	849.0	853.7	856.1	863.2	17



G5

Photometric data



© 2012 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2012, August 7
data subject to change