



MASTER LEDspot MV

MASTER LEDspotMV 7W 4200K 230V NR63 40D

Delivering a warm, halogen-like accent beam, MASTER LEDspot GU10 is ideal for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suited to public areas such as lobbies, corridors, stairwells, where the light is on 24/7. MASTER LED spot GU10 delivers huge energy savings and minimises maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. Compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement alternative for 35 and 50 W halogen lamps.

Product data

• Product Data

Order code	867466 00
Full product code	872790086746600
Full product name	MASTER LEDspotMV 7W 4200K 230V NR63 40D
Order product name	MASTER LEDspotMV 7W 4200K 230V NR63 40D
Pieces per pack	1
Packs per outerbox	6
Bar code on pack - EAN1	8727900867466
Bar code on outerbox - EAN3	8727900867473
Logistic code(s) - 12NC	929000161204
Net weight per piece	0.176 kg

• General Characteristics

Cap-Base	ES
Bulb	NR63 [NR 63mm]
Average Lifetime	45000 hr

• Electrical Characteristics

Wattage	7 W
---------	-----

Wattage Technical	7 W
Voltage	230 V
Line Frequency	50-60 Hz
Lamp Current mA	42 mA
Dimmable	Yes


• Light Technical Characteristics

Colour Code	CW
Colour Designation	Cool White
Beam Angle	40 D
Beam Description	40D [Medium beam]
Correlated Colour Temperature	4200 K
Luminous Flux	220 Lm
Luminous Intensity	320 cd
Colour rendering index	70
Luminous Efficacy Lamp	31.43 Lm/W
Colour Temperature	4200 K [CCT 4200K]

• Product Dimensions

Diameter D	63.3 mm
Overall Length C	101 mm

Dimensional drawing



Product	C (Norm)	D (Norm)
LED 7W E27 4200K 230V NR63 40D Dimmable	-	-



© 2010 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2010, August 31
data subject to change