

## DOMESTIC SOCKET OUTLET - IP54



Code	No. of poles	Rated Current	Rated voltage	Colour	Frequency	Flange dimensions (mm)	Pack Carton
<b>Standard: German</b>							
GW 62 393	2P+E	16 A	230 V	■	50/60 Hz	50x50	10/100
GW 62 392	2P+E	16 A	230 V	■	50/60 Hz	85x75	10/100
<b>Standard: French</b>							
GW 62 394	2P+E	16 A	230 V	■	50/60 Hz	50x50	10/100

CHARACTERISTICS: domestic socket-outlets equipped with child protection (shutter) and with rear connection.

NOTES: domestic socket-outlets 50x50 mm can be installed also on flanges 85x75 mm using the adapter code GW68281.

## ROUND MUSHROOM-HEAD EMERGENCY PUSH-BUTTON - MUSHROOM Ø 40MM

Code	Functions	Characteristics	Pack Carton
GW 74 361	With holding	Not illuminated	10/60

APPLICATION: suitable for emergency use, in accordance with Standard IEC 60947-5-5.

SUPPLIED: 3-seat flange (2 of which are contact-holders).

## CONTACTS - ITH=10A - 250V AC

Code	Type	Colour	Pack Carton
GW 74 501	1 NO	Green	1/30
GW 74 502	1 NC	Red	1/30
GW 74 503	2 NO	Green	1/30
GW 74 504	1 NO + 1 NC	White	1/30
GW 74 505	2 NC	Red	1/30

CHARACTERISTICS: GW74502 suitable for contact opening also in the event of slight sticking, in compliance with Standard EN 60947-5-1.

Clip assembly on the contact-holder flanges.

## CYLINDRICAL SECURITY LOCK

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys

NOTES: All the keys and relative locks with the same product code are identical.



GW62393

GW74361

GW74501

GW40422