


Flush-mounting touch switch module. Two touch areas on the front for switching an ON/OFF load (bistable/momentary function) or a timed ON load via an output contact with potential. The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol. The device has N°3 DIP-switches, located on the back of the device, for feature configuration.

Descriere	Înterupător touch	Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz
Nr. module	1	Nr. canale în intrare	2
Local control	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
Temperatură de stocare	-25 ÷ +70 °C	Nr. canale în ieșire	1
Temperatură de funcționare	-5 +45 °C	Contacte de ieșire	1 NA 5A (AC1) 240 V ac
Relative humidity (non-condensative)	Max 93%	240 V ac Incandescent-halogen lamps	Max 1000 W
Front light signaling	Led albastru	240 V ac LED lamps	Max 100 W (max 5 lamps)
Terminale de cablare	Cu șuruburi	Loads piloted from electronic transf. 240 V ac	Max 250 VA
Capacitate strângere terminal cabluri flexibile (mm ²)	Max. 1,5	240 V Fluorescent lamps	Max 120 W (max 6 lamps)
Capacitate strângere terminal cabluri rigide (mm ²)	Max. 1,5	Load control	-
Context	Dry indoor places	Acoustic signalling element	Buzzer
Clasă de protecție IP	IP20 (with plate fitted)	Standard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

