

Pagina de detalii a produsului



DX3 LEGRAND

RCBO - DX³ 6000 -10 kA -4P-400 V~ -32 A -30 mA - tip AC

REF. 411189 | EAN. 3245064111898

> [vizitați ecatalogul nostru](#)

Caracteristici tehnice

Number of poles (total)	4
Number of protected poles	4
Rated voltage	400 V
Rated current	32 A
Rated fault current	0.03 A
Leakage current type	AC
Current limiting class	1
Rated short-circuit breaking capacity according to EN 61009	6 kA
Rated short-circuit breaking capacity Icn according to EN 61009-1	6 kA
Surge current capacity	0.25 kA

Voltage type	AC
Frequency	50 Hz
Release characteristic	C
Concurrently switching neutral conductor	Yes
With interlocking device	Yes
Pollution degree	2
Width in number of modular spacings	4
Built-in depth	44 mm
Anti- nuisance tripping version	No
Degree of protection (IP)	IP20

Documentație

Document tehnică

- F01315EN-08.pdf | PDF (2.56Mo)
- LE04155AB.pdf | PDF (8.3Mo)

Acorduri & Certificate

- OC / CB-CB FR_718648 | (1.67Mo)
- LGRP-00796-V01.01-EN.pdf | PDF (0.57Mo)
- NF App Domestic-NF012_4280 | (0.77Mo)

Specificații CAD & Design / BIM

- 411189.dwg | DWG (0.17Mo)



AENOR-030/002274 | (0.56Mo)