

Lynx-L

LYNX-L 36W/830 10-WAY

0025634



Range Features

-

Lynx-L

LYNX-L 36W/830 10-WAY

0025634



PRODUCT OVERVIEW

Lamp shape	Stick
Colour temperature (K)	3000
CRI (Ra)	82
Dimmable	Referring to ballast
EAN code	5410288256344
Energy class	A
Cap/Base	2G11
Type	Lynx L
Watt (Nominal) (W)	36
Light colour	830
Ordering number	0025634
Efficacy (Rated) (lm/w)	81
Average life (Rated) (h)	16000
Luminous flux (Rated) (lm)	2950
Technology	Compact Fluorescent
Voltage (V)	106

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
CRI (Ra)	82
Light colour	830
Luminous flux (Nominal) (lm)	2950
Rated lumen maint. factor at 12000 h 50Hz	73
Rated lumen maint. factor at 16000 h 50Hz	70
Rated lumen maint. factor at 2000 h 50Hz	8500%
Rated lumen maint. factor at 4000 h 50Hz	7800%
Rated lumen maint. factor at 6000 h 50Hz	7600%

Lynx-L

LYNX-L 36W/830 10-WAY

0025634

Rated lumen maint. factor at 8000 h 50Hz	7500%
Luminous flux (Rated) (lm)	2950

General data

Average life (Nominal) (h)	16000
Control gear required	Yes
Lamp shape	Stick
Dimmable	Referring to ballast
EAN code	5410288256344
Energy class	A
General application	Retail;Hospitality;Logistics and Industry;Museums;Education;Office;Residential & Consumer;
IEC Reference	IEC 60901
IEC Reference 2	IEC 61199
Intended purpose	General lighting
Cap/Base	2G11
Lamp mercury content (mg)	<3.0
Type	Lynx L
Ordering number	0025634
Product name	LYNX-L 36W/830 10-WAY
Average life (Rated) (h)	16000
Rated survival factor at 12000 h 50Hz	0.78
Rated survival factor at 16000 h 50Hz	0.5
Rated survival factor at 2000 h 50Hz	0.98
Rated survival factor at 4000 h 50Hz	0.9
Rated survival factor at 6000 h 50Hz	0.85
Rated survival factor at 8000 h 50Hz	0.8
Special purpose lamp	No
Starting time (max) (s)	<10
Technology	Compact Fluorescent
Transformer required	Managtic ballast
Sales pack quantity	10
Warm-up time to 60% of full light (max) (s)	60
E-number FI	4940229

Electrical data

Current (A)	0.435
Ignition voltage (V)	198
kWh per 1000 hours burning time	40
Watt (Nominal) (W)	36
Efficacy (Rated) (lm/w)	81
Watt (Rated) (W)	36

Lynx-L

LYNX-L 36W/830 10-WAY

0025634


Voltage (V)	106
--------------------	-----

Physical data

Lamp Length (mm) - C/L	417.4
Length base to base (mm) - A	No
Single packaging type	Box/Sleeve
Weight (kg)	0.12
Inner package net weight (kg)	1.20
Inner package dimensions (L x W x H) (cm)	44.20 x 10.00 x 14.00
Outer package dimensions (L x W x H) (cm)	53.00 x 46.50 x 16.50
Single package dimensions (L x W x H) (cm)	43.20 x 4.50 x 2.50

TECHNICAL DRAWINGS

2G11



Lynx-L

LYNX-L 36W/830 10-WAY

0025634

