

PRODUCT DATA SHEET

Mouette Asymmetric - Fluo 2x24W + 2x54W 1900mm DALI



DESIGN BY:

Wilmotte & Industries 2004

MATERIALS:

Moulded polypropylene, aluminium

DESCRIPTION:

Single pendant with diffused lighting using 24W + 54W T16 fluorescent lamps and LED 80W. Solid opaline diffuser in moulded polypropylene. MOUETTE is available in 2 versions: symmetrical or asymmetrical. Electronic or DSI dimmable electronic ballast depending on the version. The upper part has an opening for easy installation and maintainance. Luminaire comes complete with 1900mm or 5900m long quick-adjustment steel suspension cables, ceiling plate and power cable. Light sources are included (3000K). Complies with standard EN60598-1 and other specific standards.

Height: 1900mm max.



Light emission



Dimmable

TECHNICAL DATA SHEET

FEATURES

Product name: Mouette Asymmetric - Fluo

2x24W + 2x54W 1900mm

DALI

Article Code: L860510
Colour: White opaline

Material: Moulded polypropylene,

aluminium

Series: Architectural

Area contract: Hospitality Hotel, Retail,

Office, Museum & Exihibitions

DIMENSIONS

Length:cm 195Base Width:cm 7.4Base Diameter:cm 42.4Max Height from ceiling:cm 190Weight:kg 6.8Impact Resistance:N.D.Glow Wire Test:750 °

LAMPS INCLUDED

Category: FLUO Number: 2 T16(G5) Lbs: Watt: 54W Socket: G5 FDH-54 Type: Colour Rendering: 85 Colour temperature (K): 3000K Duration (h): 20000h

 Category:
 FLUO

 Number:
 2

 Lbs:
 T16(G5)


 Watt:
 24W

 Socket:
 G5

 Type:
 FDH-24

 Colour Rendering:
 85

 Colour temperature (K):
 3000 K



COLOUR



Duration (h): 20000h

LUMINAIR

Electronic dimmable DSI integrated Power Supply:

Watt: 171.0W Voltage: 220V-240V Luminous Flux (Im): 6562lm CCT: 0K Efficiency: 53% Efficacy: 38.38lm/W

CRI: 0 Dimmable Typology: Dali

AWARDS

2005 – Design Innovationen Design Zentrum Nordrhein Westfalen _2005 Reddot Design Award "Reddot: best of the best" Essen (Deutschland)