Piazza II LED

THORN

96666256 PIAZZA II LED 1690-840 HF ANT




Piazza II LED

A robust wall mounted luminaire. Electronic, fixed output control gear. Back plate: die-cast aluminium, painted anthracite. Body: anthracite polycarbonate. Ø20mm cable entry via rear or side conduit entries, BESA compatible. IP65, IK10. Complete with 4000K LED.

Dimensions: 383 x 195 x 306 mm Total power: 15.4 W Luminaire luminous flux: 1844 lm Luminaire efficacy: 120 lm/W Weight: 2.8 kg




TLG_PIA2_F_PDB.jpg



TLG_PIA2_M_LD1.wmf

Lamp position: STD - standard Light Source: LED Luminaire luminous flux*: 1844 Im Luminaire efficacy*: 120 Im/W Lamp efficacy: 119 Im/W Colour Rendering Index min.: 80 LOR: 1,00 ULOR: 0,02 DLOR: 0,98



TLTP_PIA2_1690.ldt

Correlated colour temperature*: 4000 Kelvin Chromaticity tolerance (initial MacAdam)*: 5 Rated median useful life*: 60000h L70 at 25°C Ballast: 1x HF_ Luminaire input power*: 15.4 W Dimming: FO

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25° C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting