## а. л л. . . . . . . . . . . . . ...... а а а а J. ы л л л a a secondadad **L L L** ГГ Л J . . . . . . . . . . . ы \_\_\_ . . . . . . . . . . . . . . . . . . .








## ONE 80 DALI

## Indoor LED pendant, black, 3000/4000K

Do you want particularly pleasant, DALI dimmable light for your room in conjunction with an unusual design? This is exactly what the ONE luminaire family provides! Regardless of whether it is a wall light or a pendant, ONE will put every room is the right light. This surface-mounted wall light is sustainable and low-maintenance thanks to the anticipated service life of 30,000 hours.



## **TECHNICAL DATA**

Item no.:	1002911
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	800 mA/V
Pendant length	150.0 cm
Height	3.0 cm
Diameter	80.0 cm
Net weight	2.08 kg
Gross weight	4.55 kg
IP Code	IP 20
Safety class	1
Assembly	Surface
Assembly details	Ceiling
Dimming technology	DALI
Wattage	35 W
Lumen	2000 / 2200 lm
Colour temperature	3000/4000 Kelvin
Color	black
CRI	>80
Binning	3
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C



Maximum ambient temperature	50 °C
BIG WHITE Page	157

Notes