






ABRIDOR

Outdoor LED surface-mounted wall light IP55 anthracite 3000/4000K

The aluminium luminaires in the ABRIDOR family provide solutions for the wall light and floor stand area. Thanks to its IP55 protection class, the luminaires are suitable for outdoor use. The electrical connection is made directly to the 230V mains power supply. The unusual lamp head means that the built-in LED has particularly wide light distribution.



TECHNICAL DATA

Item no.:	1002989
Primary nominal voltage	100-277V ~50/60Hz mA/V
Secondary power / secondary voltage	300 mA/V
Length	14.0 cm
Height	16.0 cm
Depth	17.5 cm
Net weight	1.248 kg
Gross weight	1.543 kg
IP Code	IP 55
Safety class	I
Impact resistance class	IK03
Impact resistance	0,34999999999999999999999999999999999999
Assembly	Surface
Assembly details	Wall
7.000	VVali
Wattage	14 W
	1
Wattage	14 W
Wattage	14 W 750 lm
Wattage Lumen Colour temperature	14 W 750 Im 3000/4000 Kelvin
Wattage Lumen Colour temperature Color	14 W 750 Im 3000/4000 Kelvin anthracite
Wattage Lumen Colour temperature Color CRI	14 W 750 Im 3000/4000 Kelvin anthracite >80
Wattage Lumen Colour temperature Color CRI LXXBXX data	14 W 750 Im 3000/4000 Kelvin anthracite >80 70/50