



## NOYA PD PHASE

Indoor LED pendant light black CCT switch  
2700/3000K

The NOYA pendant light looks more stylish than ever indoors: in its proven elegant SLV design, it will impress you all round with a high colour rendering index (CRI>90) and a light colour (2700/3000K) that can be flexibly adjusted using the CCT switch on the top of the light. With its elongated slender shape, delicate colour details and high-quality appearance, it creates a harmonious lighting ambience in any home, as well as over tables and counters in hotels, restaurants or even cafés, for a harmonious lighting ambience. The light colour should only be selected when switched off.

## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1003530                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V               |
| Length                              | 120.0 cm               |
| Pendant length                      | 150.0 cm               |
| Width                               | 4.2 cm                 |
| Height                              | 4.0 cm                 |
| Net weight                          | 2.67 kg                |
| Gross weight                        | 2.857 kg               |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling                |
| Dimmable                            | Ja                     |
| Dimming technology                  | trailing edge          |
| Wattage                             | 32.0 W                 |
| Lumen                               | 2025 lm                |
| Beam angle                          | 115 °                  |
| Color                               | black                  |
| CRI                                 | >90                    |
| Binning                             | 5                      |
| LXXBXX data                         | 70/50                  |
| Service life                        | 50000 h                |



|                             |        |
|-----------------------------|--------|
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |

**Notes**

---

---

---

---

---