




## L-LINE OUT 50 FL POLE

Outdoor LED free-standing light horizontal anthracite  
CCT switch 3000/4000K

Whether in gardens, along the paths and driveways of residential buildings, hotels or restaurants - with its variety of lights, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members share a design vocabulary in L-shape, which stands out with its clear lines. And when it comes to lighting technology, there are no compromises: the choice of light colour (3000/4000K), which can be selected during the easy installation process, and IP protection class 65 are just some of the benefits of the L-LINE OUT.



## TECHNICAL DATA

|                                     |                           |
|-------------------------------------|---------------------------|
| Item no.:                           | 1003537                   |
| Number of different light outlets   | 1                         |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V    |
| Secondary power / secondary voltage | 350 mA/V                  |
| Length                              | 15.0 cm                   |
| Width                               | 10.0 cm                   |
| Height                              | 50.0 cm                   |
| Net weight                          | 1.95 kg                   |
| Gross weight                        | 2.087 kg                  |
| IP Code                             | IP 65                     |
| Safety class                        | I                         |
| Impact resistance class             | IK02                      |
| Impact resistance                   | 0,20000000000000001 Joule |
| Assembly                            | Surface                   |
| Assembly details                    | Ground                    |
| Wattage                             | 7.0 W                     |
| Lumen                               | 530 lm                    |
| Color                               | anthracite                |
| CRI                                 | >80                       |
| Binning                             | 6                         |
| LXXBXX data                         | 70/50                     |
| Service life                        | 30000 h                   |



|                             |        |
|-----------------------------|--------|
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C  |

### Accessories

|        |                              |
|--------|------------------------------|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
|--------|------------------------------|

### Notes

---

---

---

---

---