



OCULUS WL PHASE

Wall-mounted light black 8.5W 570lm 2000-3000K
CRI90 100° Dimmable

Thanks to its special lens optics, the OCULUS WL PHASE wall-mounted light emits a sharply delineated beam of light. The lighting features a CRI of over 90 and a dim-to-warm function (2000-3000K). Ideal for GP practices, law offices, cafés, hotels, restaurants and the private sector. In addition, the wall light can be quickly and easily connected to a 220 volt supply.

TECHNICAL DATA

Item no.	1006307
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	8.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	80
Number of luminaires at LS C16A	80
Level of inrush current	2 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.03
Lumen	57-570 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	black

Light Source

916398	
--------	---

CRI	90
LXXBXX data	L80B20
Service life	40000 h
Risk Group	1
Height	8.75 cm
Depth	12.4 cm
Diameter	9 cm
Net weight	0.63 kg
Gross weight	0.674 kg
BIG WHITE Page	355