





## FRAME BASIC

recessed fitting, LED, 3000K, square, silver-grey, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a high-quality diode and available in either pure white or warm white light colour. To operate, the FRAME BASIC needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.:	111262
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Width	9.0 cm
Height	9.0 cm
Depth	6.0 cm
Installation length	7.5 cm
Installation width	7.5 cm
Installation depth	6.6 cm
Net weight	0.242 kg
Gross weight	0.3 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	1 W
Lumen	40 lm
Colour temperature	3000 Kelvin
Color	grey
CRI	>90
LXXBXX data	70/50
Service life	30000 h

## Accessories

111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA
111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
112780	FLUSH-MOUNTED FRAME , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112781	MOUNTING BOX for FRAME BASIC , FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
464107	LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief

## Notes

---

---

---

---

---