



FRAME BASIC recessed fitting

LED, 3000K, matt white, SET, 9.4W, incl. driver

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED set is equipped with warm white Premium LED light diodes. This luminaire contains built-in LED lamps.





TECHNICAL DATA

| Lamps included Primary nominal voltage 220-240V ~50/60Hz mA/V Secondary power / secondary voltage Length 9.0 cm Width 9.0 cm Height 4.0 cm Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight IP Code IP 20 Safety class II Assembly Assembly details Ceiling, Wall | Item no.: | 112721 |
|---|-------------------------------------|------------------------|
| Secondary power / secondary voltage Length 9.0 cm Width 9.0 cm Height 4.0 cm Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight IP Code IP 20 Safety class II Assembly Recessed | Lamps included | 0 |
| Voltage 9.0 cm Width 9.0 cm Height 4.0 cm Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Width 9.0 cm Height 4.0 cm Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Secondary power / secondary voltage | 350 mA/V |
| Height 4.0 cm Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Length | 9.0 cm |
| Installation length 7.5 cm Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Width | 9.0 cm |
| Installation width 7.5 cm Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Height | 4.0 cm |
| Installation depth 5.0 cm Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Installation length | 7.5 cm |
| Net weight 0.196 kg Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Installation width | 7.5 cm |
| Gross weight 0.25 kg IP Code IP 20 Safety class II Assembly Recessed | Installation depth | 5.0 cm |
| IP Code IP 20 Safety class II Assembly Recessed | Net weight | 0.196 kg |
| Safety class II Assembly Recessed | Gross weight | 0.25 kg |
| Assembly Recessed | IP Code | IP 20 |
| | Safety class | II |
| Assembly details Ceiling, Wall | Assembly | Recessed |
| , | Assembly details | Ceiling,Wall |
| Wattage 8.6 W | Wattage | 8.6 W |
| Lumen 445 lm | Lumen | 445 lm |
| Colour temperature 3000 Kelvin | Colour temperature | 3000 Kelvin |
| Beam angle 90 ° | Beam angle | 90 ° |
| Color white | Color | white |
| CRI >80 | CRI | >80 |





| Binning | 3 |
|--------------|---------|
| LXXBXX data | 70/50 |
| Service life | 56000 h |