




NAUTILUS


outdoor spike luminaire, LED, 3000K, IP65, square, anthracite, 9W

The mobile spotlights of the NAUTILUS family are the Plug & Play best-sellers from SLV, which have enhanced a countless number of commercial and private outdoor areas for many years. The reasons are obvious: Uncompromising quality with regard to durability and flexibility. Be it harsh winter nights or warm summer evenings, a NAUTILUS outdoor fitting will adorn the garden with unmatched ambience and illuminating effects. Regardless of whether you illuminate your flowers, trees or water features with Nautilus. The NAUTILUS family has a wide range of versions with different models, designs and colours, with a plug or an open cable end, with an installation plate or an earth spike. With versions with a GU10 socket, please note the maximum dimensions and Wattages for the lamp that is going to be used (not included in scope of supply). When are you going to let yourself be impressed with the wide range of advantages of the SLV classic?



TECHNICAL DATA

Lamps included 0 Primary nominal voltage 100-240V ~50/60Hz mA/V Secondary power / secondary voltage 700 mA/V Vertical tilting range 90 ° Length 8.0 cm Length of earth spike 21.0 cm Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed Assembly details Ground	Item no.:	231035
Secondary power / secondary voltage Vertical tilting range Length 8.0 cm Length of earth spike 21.0 cm Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Lamps included	0
Vertical tilting range 90 ° Length 8.0 cm Length of earth spike 21.0 cm Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Primary nominal voltage	100-240V ~50/60Hz mA/V
Length 8.0 cm Length of earth spike 21.0 cm Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Secondary power / secondary voltage	700 mA/V
Length of earth spike 21.0 cm Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Vertical tilting range	90 °
Width 7.0 cm Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Length	8.0 cm
Height 11.7 cm Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Length of earth spike	21.0 cm
Net weight 0.89 kg Gross weight 1.105 kg IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Width	7.0 cm
Gross weight 1.105 kg IP Code IP 65 Safety class Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Height	11.7 cm
IP Code IP 65 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	Net weight	0.89 kg
Safety class Impact resistance class Ik04 Impact resistance 0,5 Joule Assembly Recessed	Gross weight	1.105 kg
Impact resistance class IK04 Impact resistance 0,5 Joule Assembly Recessed	IP Code	IP 65
Impact resistance 0,5 Joule Assembly Recessed	Safety class	I
Assembly Recessed	Impact resistance class	IK04
	Impact resistance	0,5 Joule
Assembly details Ground	Assembly	Recessed
, accounts accounts	Assembly details	Ground
Wattage 8.5 W	Wattage	8.5 W
Lumen 620 lm	Lumen	620 lm
Colour temperature 3000 Kelvin	Colour temperature	3000 Kelvin
Beam angle 45 °	Beam angle	45 °
Color anthracite	Color	anthracite



CRI	>80
Binning	6
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	621